



# FAST<sup>®</sup> CARBON

## High Cut Helmet System

- High cut, lightweight, non-ballistic shell features a hybrid design of Uni-Directional and Woven Composite Carbon Fibers.
- Designed for less extreme environments, the durable carbon construction provides protection against blunt trauma, making it ideal for rugged training, reece and water operations, and fast roping.
- Features an Ops-Core Skeleton™ Shroud for universal compatibility with most NVG mounts, 4 position Accessory Rail Connectors (ARCs) and external VELCRO<sup>®</sup> brand loop.
- Vent holes for increased ventilation and water drainage.
- Available with one suspension/retention option.

### SPECIFICATIONS

<b>Impact Testing:</b>	Anvil x2 Impact @ 10 fps (3.04 m/s) , 150 Gs
<b>Environmental Testing:</b>	Low Temp/High Temp/Sea Water/Corrosion/Flame
<b>Shell Construction:</b>	Two-stage Process: Six-Slit
<b>Areal Density:</b>	N/A
<b>Shell Thickness:</b>	0.079" (2.00 mm)
<b>Shell Geometry (Curvature):</b>	FAST Curvature
<b>Cut Style (Side Protection):</b>	High Cut

#### Available Colors:



Available Sizes	Medium	Large	X-Large	XX-Large
<b>Head Size (Circumference)</b>	20 7/8 - 22 in (53-56 cm)	22- 23 1/4 in (56-59 cm)	23 1/4 - 24 3/8 in (59-62 cm)	N/A
<b>Square Coverage</b>	153.14 in <sup>2</sup> (988 cm <sup>2</sup> )	164.77 in <sup>2</sup> (1063 cm <sup>2</sup> )	179.34 in <sup>2</sup> (1157 cm <sup>2</sup> )	N/A
<b>Shell Weight (Paint &amp; Edge Band)</b>	0.60 lbs (271 g)	0.65 lbs (297 g)	0.73 lbs (332 g)	N/A

Note: All measurements are +/- 3% tolerance

### Contact Us

**Norbo Savunma Sanayi ve Dış Ticaret Ltd. Şti.**  
Mustafa Kemal, Dumlupınar Blv. No:266B D:80  
06510 Çankaya/Ankara

Tel:+90 312 491 94 00  
Fax:+90 312 491 94 10  
info@norbo.com.tr

