



- High cut, medium weight, ballistic shell made of Monolithic Aramid.
- Allows for greater integration of communication equipment in a high cut design than ACH helmets with a low cut design.
- Features an Ops-Core 3-Point Skeleton<sup>™</sup> Shroud for universal capability with most NVG mounts, Accessory Rail Connectors (ARCs) with Hook Bungees, and external VELCRO<sup>®</sup> brand loop.
- Scalable design allows for compatibility with Ops-Core visors, mandibles, handgun face shields, and ballistic applique.
- Available with four suspension/retention options.



# **SPECIFICATIONS**

Performance Specification: Ops-Core LE Helmet Performance Specification PS-1118

Modified and Abbreviated US Army CO/PD 05-04:2007 Purchase Description

NIJ Standards: NIJ 0106.01 with NIJ 0108.01 Level IIIA (9mm FMJ / 44mag @ 1,400 ft/s) Threats

17gr FSP Fragmentation Protection: V-50 rating of 670 m/s (2,200 ft/s) in accordance with PS-1118 and MIL-STD-662F

Blunt Impact Protection: <150 G's at 10 ft/s per ACH CO/PD 05-04:2007

**Environmental Resistance:** Temperature -Storage and Operating at Ambient, Cold -60° F, and Hot +160° F, Temperature Shock, Flame Resistance, Altitude, Vibration, Seawater, Field Agent Resistance, Weatherometer per ACH CO/PD 05-04:2007

Shell Construction:	Two Stage Non Slit		
Areal Density:	2.07 lbs/ft <sup>2</sup> (101.60 g/dm <sup>2</sup> )		
Shell Thickness:	0.290" (7.37mm)		
Shell Geometry (Curvature):	Proprietary Ops-Core FAST Design		
Cut Style (Side Protection):	High Cut		
Available Colors:	Foliage Green Black		
MultiC	am® Desert MARPAT		

Available Sizes:

Medium (M), Large (L), X-Large (XL), XX-Large (XXL)

### **Contact Us**

Norbo Savunma Sanayi ve Dış Ticaret Ltd. Şti. Mustafa Kemal, Dumlupınar Blv. No:266B D:80 06510 Çankaya/Ankara

Tel:+90 312 491 94 00 Fax:+90 312 491 94 10 info@norbo.com.tr





Copyright © 2017 Gentex Corporation. Ops-Core, the Ops-Core logo, and FAST are registered trademarks of Gentex Corporation or its affiliates. Skeleton is a trademark of Gentex Corporation or its affiliates. MultiCam is a registered trademark of LineWeight LLC. VELCRO® is a registered trademark of Velcro BVBA. Used with permission.



FAST LE

## SPECIFICATIONS (CONTINUED)

#### SHELL SIZING & COVERAGE

Available Sizes	Medium	Large	X-Large	XX-Large
Head Size (Circumference)	20 7/8 - 22 in (53-56 cm)	22-23 ¼ in (56-59 cm)	23 ¼ - 24 ¾ in (59-62 cm)	24 3/8 - 25 3/8 in (62-64.5 cm)
Square Coverage	153.1 in <sup>2</sup> (988 cm <sup>2</sup> )	164.8 in <sup>2</sup> (1063 cm <sup>2</sup> )	179.3 in <sup>2</sup> (1157 cm <sup>2</sup> )	191.1 in <sup>2</sup> (1233 cm <sup>2</sup> )
SHELL WEIGHT				
Available Sizes	Medium	Large	X-Large	XX-Large
FAST LE Shell Weight (Shell with Paint & Edge Band)	2.14 lbs (969 g)	2.39 lbs (1085 g)	2.61 lbs (1184 g)	2.77 lbs (1258 g)

#### SYSTEM WEIGHT

	Suspension/Retention Option	Large
FAST LE System Weight (FAST LE Shell with Suspension/ Retention Options)	Lux Liner w/ Worm-Dial Fitband	3.35 lbs (1519 g)
	Lux Liner w/ H-Nape Chinstrap	3.24 lbs (1469 g)
	EPP Pads w/ Worm-Dial Fitband	3.20 lbs (1451 g)
	EPP Pads w/ Occ-Dial Fitband	3.25 lbs (1474 g)

Note: All measurements are +/- 3% tolerance

### **Contact Us**

Norbo Savunma Sanayi ve Dış Ticaret Ltd. Şti. Mustafa Kemal, Dumlupınar Blv. No:266B D:80 06510 Çankaya/Ankara

Tel:+90 312 491 94 00 Fax:+90 312 491 94 10 info@norbo.com.tr





Copyright © 2017 Gentex Corporation. Ops-Core, the Ops-Core logo, and FAST are registered trademarks of Gentex Corporation or its affiliates. Skeleton is a trademark of Gentex Corporation or its affiliates. MultiCam is a registered trademark of LineWeight LLC. VELCRO® is a registered trademark of Velcro BVBA. Used with permission.