



# AMP™

## Communication Headset

CONNECTORIZED VERSION

### 3-D Hear-Through and Advanced Hearing Protection in a Mission Configurable Design

Ops-Core headsets are designed to maintain natural hearing and sound localization. Advanced 3D Hear-Through technology and hearing protection capabilities in the Ops-Core AMP (Adaptive Mission Platform) Communication Headset further enhance situational awareness and user safety. For optimal flexibility and performance, the modular headset can be easily configured to meet a wide range of mission needs with options for headband or helmet mounted use, single or double hearing protection, single or multi-channel communications, and changeable Camo Skin Sets.



## KEY FEATURES

### ■ World Class Audio Quality

Leveraging industry-leading military and industrial safety hearing protection and communication systems' capabilities of parent company Gentex Corporation, the Ops-Core AMP Communication Headset provides unprecedented audio quality with the ability to operate in combat environments.

### ■ 3D Hear-Through (3DHT)

Restores and enhances "natural hearing" of outside environment for improved situational awareness. Ear-simulator design reproduces ambient sounds with a high degree of directional accuracy, while also providing robust hearing protection.

### ■ Optional NFMI (Near Field Magnetic Induction) Earplugs (sold separately)

Provide increased noise reduction, while maintaining clear communications and 3D Hear-Through ability. NFMI Earplugs do not require wires or batteries. NOTE: Compatible with NFMI-enabled headsets only.

### ■ Quick-Release Download Connections

Disconnect headset from download(s) to allow for set up on left, right, or both sides. System can quickly configure between single, dual, or no download. Easy to use Push to Talk (PTT) connection permits secure, clear audio transmission in high noise environments.

### ■ Earseals

Ergonomically designed to fit head geometry, providing better seal and increased noise attenuation.

### ■ Auto Shut-Down

To preserve battery life, alert tones signal 3DHT shut down after two hours of inactivity. Pressing volume button resets timer. Included AAA lithium batteries provide 120 hours of 3DHT use.

### ■ Mission Configurable Capability

Dual configuration capability adapts headset to either headband or helmet-mounted preference based on operational requirements.

#### Ergonomic Headband

Engineered for optimal comfort and streamlined profile; capable of being worn under a helmet. Quick attach/detach from headband capability.

#### Rail Mount Kit (sold separately)

Optional rail arms can be mounted to rear of Ops-Core ARCs, leaving top portion of rails free for other accessories, while increasing helmet stabilization and providing a counterbalancing effect of shroud mounted devices. Single point gimbal attachment to earcups allows for 360° adjustment, providing a better earseal and accommodation of head movement. Rotate earcups to side or rear of helmet to create low profile, streamlined stowage when not in use.

### ■ Noise-Cancelling Microphone

Mitigates background noise enabling clear communication. Can be mounted to left or right earcup or removed as preferred.

### ■ Integrated Microphone Mounting & Connection Point

Enables easy integration with any U-173/U standard plug.

### ■ Fail-Safe Communications

In the event of battery loss, 3DHT will power off leaving headset and earplugs to operate for standard communication.

### ■ Camo Skin Sets (sold separately)

To suite your mission, choose from a comprehensive suite of optional Skin Sets available in Arid, Tropic, Alpine, Black, and standard MultiCam®.



## AMP Communication Headset

### SPECIFICATIONS

#### Noise Protection Ratings:

Headset Alone:	NRR 22 dB
	SNR 27 dB
	H 31 dB
	M 23 dB
NFMI Version (when used with optional NFMI Earplugs):	L 19 dB
	NRR 34 dB
	SNR 41 dB
	H 41 dB
	M 39 dB
	L 34 dB

**Battery Run Time:** Up to 120 Hrs w/ Lithium Batteries @ 21°C

**Battery Run Time w/ NFMI Engaged :** Up to 80 Hours w/ Lithium Batteries @ 21°C

**Salt Water Immersion:** IPX7

**Environmental:** MIL-STD-810G

**Operating Temperature:** -40°C to +55°C (-40°F to +131°F) w/ Lithium Batteries

**Storage Temperature:** -40°C to +71°C (-40°F to +160°F)





**EMI Testing Standards** MIL-STD-461G

#### Weight\*:

Headband Configuration	0.85 lbs (386 g)
NFMI Headband Configuration	0.92 lbs (419g)
Rail Mounted Configuration	0.94 lbs (426g)
NFMI Rail Mounted Configuration	1.01 lbs (460g)

*\*Weights calculated with batteries*

#### Manufacturer Part Number:

 Tan 499, Connectorized, NFMI N101153-02-0000	 Black, Connectorized, NFMI N101153-02-0001
Tan 499, Connectorized N101153-01-0000	Black, Connectorized N101153-01-0001
 Foliage Green, Connectorized, NFMI N101153-02-0002	 Urban Gray, Connectorized, NFMI N101153-02-0003
Foliage Green, Connectorized, N101153-01-0002	Urban Gray, Connectorized N101153-01-0003

### Contact Us

**Norbo Savunma Sanayi ve Dış Ticaret Ltd. Şti.**  
Mustafa Kemal, Dumlupınar Blv. No:266B D:80  
06510 Çankaya/Ankara

Tel:+90 312 491 94 00  
Fax:+90 312 491 94 10  
info@norbo.com.tr



[www.norbo.com.tr](http://www.norbo.com.tr)